

Z-POS Series

“Always right there in front of your payments and transactions”

- The industry's premier point of sale solution for retailers
- Product reliability & safety
- Easy to install and maintain POS systems
- Green IT of low energy consumption



Fan Free, Tool Free Z-POS

The Best hit model Z-POS has the powerful features and smart design.



The Best hit model Z-POS has the powerful features and smart design. Z-POS is two-tone black and white, curved edges for a modern look and focuses on a user-friendly design. The first product in Korea adopts the frame Touch technology and 9.7-inch Dual Monitor option. The I/O (input/output) ports have been placed on the top of the panel, to aid ease of installation and hide cabling. Z-POS has adopted hand-screws to the MSR, HDD and Main Board to further increase ease of installation, servicing and user friendliness.



User Friendly Design
Stylish All-in-one design with 9.7-inch dual monitor



Easy to Service
I/O ports are placed on the top of the panel

Z-1500
Normal Touch Type



Z-9000
Frame Touch Type



Z-POS Series, Stylish POS System

- No Fan, No Noise
- Product reliability & safety
- Easy to install and maintain with Fingertip screws
- Hidden Adapter and cables
- Waterproof and dust resistant LCD panel
- Green IT of low energy consumption

Product reliability & safety
Proven product reliability and safety through EMC test, KCC, CE & FCC by Authorized Testing and Certification Bodies



Green IT
Intel Atom processor offers low power consumption. Low energy consumption can reduce unnecessary heat and expand the life span of POS components.



Specification

| Item | Specification | |
|-----------------------------|-------------------------------------|--|
| Main | Formfactor | 170 mm (W) x 170 mm (L) : Mini ITX Platform |
| | CPU | Onboard Intel Atom Processor Dual Core D2550 (1M Cache, 1.86 GHz) |
| | Chipset | Intel NM10 Express Chipset |
| | Memory | DDR3 SODIMM 2GB (up to 4GB by 2 x Slots) |
| | Storage | 2.5" SATA 320GB HDD |
| Primary Display | LCD | 15-inch TFT LED LCD, LVDS interface |
| | Resolution | 1024 x 768 |
| | Touch | 15" 5-Wire Analog Resistive Touch (Serial I/F) |
| Indicator | 2 x LEDs and 1 x Buzzer | |
| Speaker | 1 x 1W | |
| I/O Port | USB | 6 ports (2 x Side, 4 x Rear) |
| | Serial | 4 RS-232C ports (3 x Powered DSUB-9, 1 x RJ-45) COM1/4 : 0/5/12V By Jumper, COM2/3 : 0/5/12V By BIOS Select |
| | PS/2 | 2 ports (1 x Mouse, 1 x Keyboard) |
| | LAN | 2 Gigabit LAN ports |
| | VGA | 1 VGA port |
| | Audio | 2 ports (1 x Mic-in, 1 x Line-out) |
| Power | DC-IN | External 60W Adapter Input AC 100~240V/ 50~60Hz, Output DC 12V/5A |
| Dimension | W x D x H mm | 389 x 206 x 322 |
| Tilt Adjustment | 0°~50° | |
| WEIGHT | 6.25kg / 7.47kg (with Dual Monitor) | |
| User Environment | Temperature | Operating -25 to 65 Storage -35 to 75 |
| | MSR | ISO 1,2,3 Tracks Reading |
| Optional Peripherals | OS | POSReady2009 / POSReady7 |
| | Storage | SSD 32GB / 64GB / 128GB |
| | 2nd Display | 9.7-inch TFT LCD (1024 X 768) 9.7-inch TFT LCD (Touch Screen) |

This specification can be changed without Prior notice

ver. ZPOS_201307_EA

