

# K-9000

“Touch the world best POS system, K-POS Series”

K-9000 is designed to provide outstanding performance for your business and to protect your business.



www.okpos.co.kr

K-POS Series



OKPOS's POS terminals are undefeated in innovation and have a solid commitment in providing the optimum combination of performance and value. K-9000 is designed to provide outstanding performance for your business and to protect your business. OKPOS's POS terminals are designed to accelerate customer service and K-9000 shows business-optimized technologies, innovative design.



#### High Performance

- High-performance CPU loaded
- Vivid high-definition screen using LED technology
- Low-noise and low-heat using fan-less type



#### Stylish Design

- Polished appearance of having tender curve



#### Slim & Compact

- Ultra-thin and sleek exterior



#### Simple & Easy Maintenance

- Easy assembly & disassembly without tools
- Convenient access to Mother Board

#### K-9000

- Premium POS system designed for hospitality and retail
- Combined high technology and sleek design
- Maximum reliability
- Industry-leading durability and serviceability
- Vivid LED screen for the best view
- Tools-free maintenance with great ease



#### Product reliability & safety

Proven product reliability and safety through EMC test, KC, CE & FCC by Authorized Testing and Certification Bodies

#### Green IT

Low energy consumption can reduce unnecessary heat and expand the life span of POS components.



#### Specification

Item	Specification		
Main	Formfactor	170 mm(W) x 170mm(L); Embedded Mini ITX Platform	
	CPU	Onboard Intel Celeron 1037U 1.8GHz (Dual Core)	
	Chipset	Intel NM70 Express Chipset	
	Memory	DDR3 SODIMM 2GB (up to 8GB by 2 x Slots)	
	Storage	2.5" SATA- II 320GB HDD	
Primary Display	LCD	15-inch TFT LED LCD (350cd), LVDS Interface	
	Resolution	1024 x 768	
	Touch	15-inch 5-Wire Resistive Frame Type, Serial Interface	
I/O Port	Indicator	2 x LED	
	Speaker	1 x 1W	
	USB	6 x USB (Rear: 4 x USB, Side: 2 x USB)	
	Serial	4 x RS-232C (3 x Powered DSUB-9, 1 x RJ-45)	
		COM 1~4: 0/5/12V by BIOS select	
	PS/2	1 x Keyboard or Mouse	
	LAN	1 x Gigabit LAN	
	VGA	1 x RGB	
Power	DC-IN	External 60W Adapter	
		Input AC 100~240V/50~60Hz, Output DC 12V/5A	
User Environment	Temperature	Operating -25 to 65, Storage -35 to 75	
Size	Dimension	341 x 345 x 209 (WxDxH)	
	Weight	6.6 Kg (without MSR) / 6.9 kg (with MSR)	
	MSR	ISO 1,2,3 Tracks Reading	
Optional Peripherals	OS	POSReady2009 / POSReady7	
	Storage	SATA-III HDD 320GB / SSD 64GB	
	2nd Display		15-inch LED LCD (1024 x 768)
			9.7-inch TFT LCD (1024 x 768)

This specification can be changed without Prior notice

**OKPOS**  
No.1 Total Solution Provider

# 801-802, Ace High-end Tower 6th, Gasan-dong, Geumcheon-gu, Seoul, Korea (153 - 801)  
Tel +82-1566-9051, Fax +82-2-6299-5447, URL www.okpos.co.kr/eng

Ver: KPOS\_201312\_EA



made in Korea

**K-9000**  
www.okpos.co.kr

